



Esso PG82

Esso Asphalt , Singapore

Polymer Modified Asphalt

Product Description

Esso PG82 is a polymer modified asphalt. It contains a specific mixture of polymers that can provide additional resistance to rutting and cracking.

Applications

Esso PG82 is used in hot mix asphalt for use on heavy traffic roads, airport pavements and other similar applications. Please consult supplier for specific usage and handling details.

Properties and Specifications

Property	Unit of Measure	Test Method	Min Limit	Max Limit
Viscosity @ 135 °C	Pa.s	ASTM D4402		3
Dynamic Shear Rheometer, G*/sin d, 82 C, Unaged Material	kPa	AASHTO T 315	1.0	
Softening Point	C	ASTM D36	80	
Dynamic Shear Rheometer, G*/sin d, 82 C, Rolling Thin Film Aged Material	kPa	AASHTO T 315	2.2	
Flash Point, Cleveland Open Cup	C	ASTM D92	230	
Elastic recovery at 25°C, 10 cm elongation	% of new	ASTM D6084	80	
Storage stability, difference in softening point	C	EN 13399		5
Mass Change, RTFO residue	% Loss	ASTM D2872		1.0

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2025

ExxonMobil

Exxon Mobil 

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved

