ExxonMobil

AP SN 800

ExxonMobil Basestocks , Australia

Product Description

ExxonMobil AP SN 800 base stock is suitable for broad blending coverage with performance capabilities in finished lubricants, especially, in Cylinder Oil marine applications. Along with other base stocks, and base stock slates, it is part of the offering that makes ExxonMobil the recognized market leader for Group I base stocks.

This Special Application base stock is available by vessel.

Features and Benefits

Consistent base stock formulations help simplify operations. These specialized base stocks by ExxonMobil simplify our customers' operations because we produce varying viscosity base stocks with consistent quality following our proprietary Product Quality Management System (PQMS) standards. Procurement and supply chain managers count on us to deliver the base stocks they need, when and where they need them. Benefits include:

• Unique stocks tailored to applications

• Consistence performance in formulations

• Superior supply chain/delivery logistics

Specifications

Property	Limit	Standard Method(a)	
Conradson Carbon Residue, mass%	Max	ASTM D189	0.3
Viscosity Index	Min	ASTM D2270	85
Kinematic Viscosity @ 100 C, mm2/s	Min-Max	ASTM D445	12.5-16.0
Flash Point, Cleveland Open Cup, °C	Min	ASTM D92	246
Pour Point, °C	Max	ASTM D97	-6
Appearance	Min-Max	Visual	Clear and Bright

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit used in expressing the limiting value in accordance to the ASTM E 29 method

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2019

Mobil Oil Australia Pty Ltd
664 Collins Street,
Docklands, Victoria, 3008,
Australia
1800 105 961 or +61 3 9261 0000
http://www.exxonmobil.com

All products may not be available in all countries. Every care has been taken in the preparation of this information. Typical values may vary within modest ranges and specifications may be subject to change. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names which include Esso, Mobil, Exxon, or ExxonMobil. For convenience and simplicity, the term ExxonMobil may be used to represent all of these entities, and the products and services provided by those entities. Nothing in this brochure is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with local ExxonMobil-affiliated entities.

ExxonMobil

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved