



Mobilgard™ HSD CH-4

ExxonMobil Marine , 中国

High Speed Diesel Engine Oil

Product Description

Mobilgard™ HSD 15W-40/20W-50 CH-4 products are high performance diesel engine oils that provide reliable protection of diesel engines operating in marine severe service applications. Mobilgard HSD 15W-40/20W-50 CH-4 products are recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments in marine industries.

Features and Benefits

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Clean engines and long engine life
Component compatibility	Long seal and gasket life

Applications

Mobilgard HSD 15W-40/20W-50 CH-4 products are designed to provide reliable engine protection in the most severe service marine applications of both modern marine diesel engines as well as older models in marine industry such as inland, coastal, dredging, fishing, passenger, offshore service and others.

Specifications and Approvals

This product has the following approvals:	MOBILGARD HSD 15W-40 CH-4	MOBILGARD HSD 20W-50 CH-4
MTU Oil Category 2	X	

This product is recommended for use in applications requiring:		
API CF	X	X
API CF-4	X	X
API CG-4	X	X
API SJ	X	X
Mack EO-M	X	

This product is recommended for use in applications requiring:		
MAN M 3275-1	X	X
VOLVO VDS		X
VOLVO VDS-2	X	

This product meets or exceeds the requirements of:		
API CH-4	X	X
Cummins CES 20076	X	

Properties and Specifications

Property	MOBILGARD HSD 15W-40 CH-4	MOBILGARD HSD 20W-50 CH-4
Grade	SAE 15W-40	SAE 20W-50
Ash, Sulfated, mass%, ASTM D874	1.1	1.1
Density @ 15 C, kg/l, ASTM D4052	0.87	
Density @ 15.6 C, g/ml, ASTM D4052		0.87
Flash Point, °C, ASTM D92		245
Flash Point, Cleveland Open Cup, °C, ASTM D92	233	
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	15.2	20.2
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	115.9	174.4
Pour Point, °C, ASTM D97	-33	-30
Total Base Number, mgKOH/g, ASTM D2896	8.5	9.0
Viscosity Index, ASTM D2270	137	135

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2023

ExxonMobil Marine Limited

Ermyrn Way

Leatherhead, Surrey

United Kingdom KT22 8UX

<http://www.exxonmobil.com>

Due to continual product research and development, the information contained herein is subject to change without notification.

Typical Properties may vary slightly.

ExxonMobil

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved