



Mobil Super™ 3000 Hybrid Series

Mobil Passenger Vehicle Lube , Argentina

Synthetic Motor Oil for Gasoline and Hybrid Engines

Product Description

Mobil Super™ 3000 Hybrid Series are synthetic motor oils, which provide excellent high temperature protection even under severe operating conditions. Mobil Super™ 3000 Hybrid Series are designed to help provide long engine life and outstanding protection in vehicles of all ages. Mobil Super™ 3000 Hybrid Series provide outstanding protection against sludge, engine rust and corrosion under severe and low-temperature operating conditions and provides optimum viscosity and fluidity across a broad range of temperatures.

Mobil Super™ 3000 Hybrid Series are recommended by ExxonMobil for use in applications requiring API SQ and ILSAC GF-7A.

Features and Benefits

- Helps extend engine life
- Outstanding wear protection for vehicles of all ages
- Excellent high temperature protection to help keep engines cool
- Permits extended operation at elevated temperatures (up to 400° F) without oxidative oil thickening and oil breakdown
- Helps control oil consumption and loss
- Allows easy starting and rapid oil circulation during cold starts to protect critical engine parts

Applications

Mobil Super™ 3000 Hybrid Series are recommended for both hybrid and other modern vehicles where they will help provide the performance required even under very demanding driving conditions.

- Latest gasoline engine technologies including high performance, turbo-charged, direct injection and hybrids found in passenger cars, SUVs, light vans and trucks
- Severe and low-temperature operating conditions

Specifications and Approvals

This product meets or exceeds the requirements of:	MOBIL SUPER 3000 HYBRID 0W-20	MOBIL SUPER 3000 HYBRID 5W-30
API SN	X	X
API SN PLUS	X	X
API SP	X	X
API SQ	X	X
ILSAC GF-6A	X	X
ILSAC GF-7A	X	X

Properties and Specifications

Property	MOBIL SUPER 3000 HYBRID 0W-20	MOBIL SUPER 3000 HYBRID 5W-30
Grade	SAE 0W-20	SAE 5W-30
Appearance, AMS 1738	Clear & Bright	Clear and Bright
Density @ 15 C, g/ml, ASTM D4052	0.848	0.849
Flash Point, Cleveland Open Cup, °C, ASTM D92	235	237
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.4	10.7
Pour Point, °C, ASTM D97	-42	-42
Viscosity Index, ASTM D2270	168	166

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2025

Cosan Lubricantes S.R.L.

Av. Libertador 6343, Piso 8

CABA, CP 1498, Buenos Aires – Argentina

0800 345 79540

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved