



Mobil Super™ 3000 Formula P 0W-20

Mobil Passenger Vehicle Lube , Austria

High Protection Engine Oil

Product Description

Mobil Super™ 3000 engine oil series are synthetic and engineered to deliver outstanding protection.

Mobil Super 3000 Formula P 0W-20 is a new generation low ash–low viscosity engine oil formulated for the specific needs of Stellantis/ PSA most recent gasoline, diesel and hybrid vehicles. Mobil Super 3000 Formula P 0W-20 high protection engine oil holds PSA B71 2010 approval.

Features and Benefits

Mobil Super 3000 Formula P 0W-20 is designed to help:

- Modern gasoline, diesel and hybrid engines operate according to improved fuel economy and emission reduction targets
- Protect emission after-treatment systems from poisoning and clogging for long-life effectiveness (oil formula has reduced phosphorus, sulfur and metals (ash))
- Protect engines from deposits and sludge build-up for effective engine cooling and lubrication
- Preserve long engine life thanks to rapid start-up and effective protection of engines equipped with stop-start technology, even at cold temperature

Applications

Mobil Super 3000 Formula P 0W-20 is recommended for modern high efficiency gasoline, diesel and hybrid cars from Peugeot, Citroën, DS, and Opel (Vauxhall in the UK). This oil is recommended in particular for PSA DV5R and EB2DT engines with BlueHDi or PureTech technologies. Mobil Super 3000 Formula P 0W-20 is not appropriate for prior generation engines designed to operate with higher viscosity engine oils.

Owner's manual should be consulted for recommended viscosity grade and specification.

Specifications and Approvals

This product has the following approvals:

PSA B71 2010

This product is recommended for use in applications requiring:

FIAT 9.55535-DM1

FIAT 9.55535-DSX

This product meets or exceeds the requirements of:

ACEA C5

Properties and Specifications

Property	
Grade	SAE 0W-20

Property	
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	42.8
Viscosity Index, ASTM D2270	170
Density @ 15 C, g/ml, ASTM D4052	0.846
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	229

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2025

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BVBA.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)
 POLDERDIJKWEG
 B-2030 Antwerpen
 Belgium

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved