



## Mobil Super 2000 5W-30 and 10W-30

Mobil Passenger Vehicle Lube , Barbados

Premium Semi-Synthetic Passenger Vehicle Engine Oil

### Product Description

Mobil Super 2000 5W-30 and 10W-30 are enhanced-premium semi-synthetic motor oils meeting the latest industry engine oil specifications. They are designed to provide an excellent level of protection and performance under the most demanding conditions.

### Features and Benefits

Mobil Super 2000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 2000 5W-30 and 10W-30 contain low friction semi-synthetic formulation which increases engine efficiency and offers greater fuel economy. Mobil Super 2000 5W-30 and 10W-30 helps to promote long engine life.

Mobil Super 2000 provides:

- Thanks to its semi-synthetic formulation provides improved fuel economy up to a 3%\* by enabling the engine to work more efficiently
- Its additive package provides excellent protection against engine wear and deposit formation.
- Provides superior engine protection during start up
- Excellent high temperature protection thanks to its high quality base oil formulation

### Applications

Mobil Super 2000 5W-30 and 10W-30 products are formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Latest gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Stop and Go City Driving
- Normal to severe operating conditions
- Turbo-Chargers
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

This product is recommended by ExxonMobil for use in applications requiring:	5W-20	5W-30	5W-40	10W-30
API CF			X	

This product is recommended for use in applications requiring:	5W-20	5W-30	5W-40	10W-30
API CF	X	X		
API Energy Conserving (SM)		X		X
ILSAC GF-4	X	X		X

This product meets or exceeds the requirements of:	5W-20	5W-30	5W-40	10W-30
API SJ		X		X
API SL		X		X
API SM	X	X	X	X
API SN	X	X	X	X
API SN Resource Conserving		X		X
ILSAC GF-5	X	X		X
Chrysler MS-6395		X		

### Properties and Specifications

Property	5W-20	5W-30	5W-40	10W-30
Grade	SAE 5W-20	SAE 5W-30	SAE 5W-40	SAE 10W-30
Ash, Sulfated, mass%, ASTM D874	0.8	0.8	0.8	0.82
Density @ 15 C, g/ml, ASTM D4052	0.85	0.86	0.86	0.8665
Flash Point, Cleveland Open Cup, °C, ASTM D92	220	220	220	220
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683			3.7	
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.6			3.14
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	8.5	10.5	14	10.4
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	48	62	85	66.3
Pour Point, °C, ASTM D97	-30	-33	-33	-33
Viscosity Index, ASTM D2270	155	160	170	145

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

**ExxonMobil**

Exxon Mobil ESSO

© Copyright 2003-2026 Exxon Mobil Corporation. All

06.06.2026

Rights Reserved