



## Mobil™ Hidráulico AW HLP Series

Mobil Industrial , Brazil

Hydraulic Oils

### Product Description

Mobil™ Hidráulico AW HLP Series oils are good quality anti-wear hydraulic oils intended for industrial and mobile service applications, subjected to moderate operating conditions and requiring anti-wear lubricants.

Their effective oxidation resistance and chemical stability support good oil life in moderate applications.

### Features and Benefits

Good anti-wear performance helps reduce pump wear and prolonging pump life.

Corrosion protection helps reduce the effects of moisture on system components.

Filterability to prevent filter blockage even in the presence of water.

### Applications

Systems using gear, vane, radial and axial piston pumps and those containing gears and bearings where mild anti-wear characteristics are required.

Where hydraulic oil contamination or leakage is unavoidable.

Where small amounts of water are unavoidable.

### Specifications and Approvals

This product meets or exceeds the requirements of:	MOBIL HIDRAULICO AW 46 HLP	MOBIL HIDRAULICO AW 100 HLP	MOBIL HIDRAULICO AW 68 HLP
DIN 51524-2:2017-06	X	X	X
ISO L-HM (ISO 11158:2023)			X

### Properties and Specifications

Property	MOBIL HIDRAULICO AW 46 HLP	MOBIL HIDRAULICO AW 100 HLP	MOBIL HIDRAULICO AW 68 HLP
Grade	ISO 46	ISO 100	ISO VG 68
Appearance, AMS 1738	Clear and Bright	Clear and Bright	Clear and Bright

Property	MOBIL HIDRAULICO AW 46 HLP	MOBIL HIDRAULICO AW 100 HLP	MOBIL HIDRAULICO AW 68 HLP
Copper Strip Corrosion, 3 h, 100 C, Rating, ASTM D130	1A	1A	1A
Density @ 15 C, kg/l, ASTM D1298	0.8765	0.8845	0.8825
Flash Point, Cleveland Open Cup, °C, ASTM D92	240		195
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	6.7	11.1	8.5
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	46	100	68
Pour Point, °C, ASTM D97	-30	-24	-27
Rust Characteristics, Procedure B, ASTM D665	Pass	Pass	Pass
Viscosity Index, ASTM D2270	95	95	95

## Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2025

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01

21930-080 Rio de Janeiro – RJ - BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved