



Mobil Super™ 3000 Formula DD 5W-30

Mobil Passenger Vehicle Lube , Brazil

Fully Synthetic Engine Oil

Product Description

Mobil Super™ 3000 Formula DD 5W-30 is a full synthetic engine oil, which provides excellent high temperature protection even under severe operating conditions. This product is designed to help provide long engine life and outstanding protection in vehicles of all ages. Mobil Super™ 3000 Formula DD 5W-30 provides outstanding protection against sludge, engine rust and corrosion under severe and low-temperature operating conditions and provides optimum viscosity and fluidity across a broad range of temperatures.

Features and Benefits

- Helps extend engine life
- Outstanding wear protection for vehicles of all ages
- Excellent high temperature protection to help keep engines cool
- Helps control oil consumption and loss
- Allows easy starting and rapid oil circulation during cold starts to protect critical engine parts

Applications

Mobil Super 3000 Formula DD 5W-30 is recommended for gasoline or ethanol fueled automobiles where a 5W-30 viscosity is required.

Mobil Super 3000 Formula DD 5W-30 is also recommend for vehicles equipped with diesel engines that previously used GM dexos2 where a 5W-30 viscosity is required.

Mobil Super 3000 Formula DD 5W-30 engine oil meets or exceeds the performance of GM dexosD engine oils and are backward compatible with GM dexos2.

Specifications and Approvals

This product has the following approvals:
GM dexosD Licensed

This product meets or exceeds the requirements of:
API SP
ILSAC GF-6A
ACEA C2

Properties and Specifications

Property	
-----------------	--

Property	
Grade	SAE 5W-30
Flash Point, Cleveland Open Cup, °C, ASTM D92	224
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	9.7
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	55.2
Density @ 15 C, g/ml, ASTM D4052	0.8508
Pour Point, °C, ASTM D97	-39

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2024

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01

21930-080 Rio de Janeiro – RJ - BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved