Mobil Super™ 2000 10W-40

Mobil Passenger Vehicle Lube , Chile

Mobil passenger-vehicle-lube

Product Description

Mobil Super 2000 10W-40 is an enhanced-premium semi-synthetic motor oil meeting the latest industry engine oil specifications. It is designed to provide an excellent level of protection and performance under the most demanding conditions.

Features and Benefits

Features	Advantages and Potential Benefits
Excellent engine cleanliness	
Excellent high temperature protection	
Improve engine efficiencies by reducing Engine Low Speed Pre-Ignition (LSPI)	

Applications

Mobil Super 2000 10W-40 is formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Latest gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Stop and Go City Driving
- Normal to severe operating conditions
- Turbo-Chargers
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle

Specifications and Approvals

This product meets or exceeds the requirements of:
API SL
API SM

This product meets or exceeds the requirements of:
API SN
API SN PLUS
API SP

Properties and Specifications

Property	
Grade	SAE 10W-40
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	224
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	113
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	15.7
Density @ 15.6 C, g/ml, ASTM D4052	0.867

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2021
COPEC S.A.

Isidora Goyenechea 2915, Las Condes, Santiago Chile

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved