



## Mobil Super™ 1000 5W-40

Mobil Passenger Vehicle Lube , 中国

Synthetic Technology Engine Oil

### Product Description

Mobil Super™ 1000 5W-40 is premium synthetic technology motor oil designed to provide everyday protection for cars under most operating conditions.

### Features and Benefits

Mobil Super™ 1000 5W-40 is meticulously engineered for today's tougher engine specifications. It provides reliable engine protection in everyday driving and helps to extend engine life.

- Designed to provide reliable anti-wear protection
- Helps to maintain engine cleanliness

### Applications

Mobil Super™ 1000 5W-40 is suitable for use in gasoline powered vehicles, and is ideally suited for less stressful driving conditions such as highway driving and lower consistent speed conditions in everyday driving.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

This product meets or exceeds the requirements of:
API SP
API SN PLUS
API SN

### Properties and Specifications

Property	
Grade	SAE 5W-40
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Ash, Sulfated, mass%, ASTM D874	0.77
Density @ 15.6 C, g/ml, ASTM D4052	0.854
Viscosity Index, ASTM D2270	163

Property	
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.6
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.4
Total Base Number, mgKOH/g, ASTM D2896	7.1
Pour Point, °C, ASTM D97	-45
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	28900
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	92

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2024

ExxonMobil (China) Investment Co. Ltd  
 17th Floor, Metro Tower  
 30 Tian Yao Qiao Road  
 Shanghai 2000030  
 China


+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved