



## Mobil Super™ 2000 Synthetic 5W-40

Mobil Passenger Vehicle Lube , 中国

Full Synthetic Engine Oil

### Product Description

Mobil Super™ 2000 Synthetic 5W-40 is full synthetic engine oils, designed to provide fast protection for engines against tough conditions in city driving.

### Features and Benefits

Excellent anti-wear protection for vehicles of all ages against tough conditions in city driving.

Excellent protection against harmful deposits to maintain engine cleanliness.

Low temperature fluidity for smooth start-up, plus exceptional viscosity stability at high operating temperatures.

### Applications

Mobil Super™ 2000 Synthetic 5W-40 is formulated to give you confidence of engine protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Passenger cars, SUV's, and high performance vehicles
- Engines with Turbo-Chargers
- Highway cruising
- Normal to occasionally severe operating conditions
- Stop and Go City Driving

### Specifications and Approvals

**This product is recommended for use in applications requiring:**

API CF

**This product meets or exceeds the requirements of:**

API SN

API SN PLUS

API SP

### Properties and Specifications

Property	
Grade	SAE 5W-40
Ash, Sulfated, mass%, ASTM D874	0.7

Property	
Flash Point, Cleveland Open Cup, °C, ASTM D92	232
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	93
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.6
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.5
Density @ 15.6 C, g/ml, ASTM D4052	0.852
Viscosity Index, ASTM D2270	161
Total Base Number, mgKOH/g, ASTM D2896	6.1
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	30600
Pour Point, °C, ASTM D97	-42

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2025

ExxonMobil (China) Investment Co. Ltd  
17th Floor, Metro Tower  
30 Tian Yao Qiao Road  
Shanghai 2000030  
China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

Exxon Mobil 

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved