Mobil

Mobil Super™ Ultimate Protection A3/B4 5W-40

Mobil Passenger Vehicle Lube , Cyprus

Advanced Synthetic Technology Engine Oil

Product Description

Mobil Super™ Ultimate Protection A3/B4 5W-40 is an advanced synthetic technology engine oil that provides long engine life for various types and ages of vehicles, offering enhanced protection across a wide temperature range.

Features and Benefits

Mobil Super™ Ultimate Protection products are industry proven so you can trust you will get the protection you want from your vehicle. Mobil Super™ Ultimate Protection A3/B4 5W-40 provides:

• Robust oil film protection at high temperatures
• Reliable cold start-up protection
• Advanced engine cleanliness and sludge prevention
• Excellent wear protection

Applications

Mobil Super™ Ultimate Protection products are formulated to give you confidence in protection beyond that of conventional or semi-synthetic oils. ExxonMobil recommends Mobil Super™ Ultimate Protection A3/B4 5W-40 if you regularly experience demanding conditions, as it can help combat the damage caused by frequent high engine stress.

- Passenger cars, SUV's, light trucks and vans
- Gasoline and Diesel engines, without emission aftertreatment systems
- High performance engines with turbo-chargers and direct injection
- Highway cruising and stop and go city driving
- Normal to frequently severe operating conditions

Always consult your owner's manual to check the recommended viscosity grade and specifications.

Specifications and Approvals

This product has the following approvals:
RENAULT RN0700
RENAULT RN0710

Properties and Specifications

Property	
Grade	SAE 5W-40
Viscosity Index, ASTM D2270	169
Density @ 15.6 C, g/ml, ASTM D4052	0.847
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	13.2
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	79
Flash Point, Cleveland Open Cup, °C, ASTM D92	236

Property	
Pour Point, °C, ASTM D97	-39

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2026

.

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved