



Mobil™ Multigrade 20W-50

Mobil Passenger Vehicle Lube , Egypt

High Quality Motor Oil

Product Description

Mobil™ Multigrade 20W-50 engine oil is formulated from quality base stocks combined with modern performance additives to provide the engine protection and performance under a wide variety of operating conditions.

Mobil™ Multigrade 20W-50 is a high quality engine oil suitable for use in all vehicles types and suitable for use in dual fuel engines (Gasoline/CNG).

Features and Benefits

- Helps reduce engine wear and corrosion
- Helps keep engine clean
- Multigrade motor oil allowing easier starts at low temperatures
- Good high temperature properties

Applications

Recommended by ExxonMobil for use in applications requiring API SF/CC

Specifications and Approvals

This product is recommended for use in applications requiring:

API CC

API SF

Properties and Specifications

| Property | |
|--|------------|
| Grade | SAE 20W-50 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 254 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 18.77 |
| Total Base Number, mgKOH/g, ASTM D2896 | 9 |
| Viscosity Index, ASTM D2270 | 134 |
| Cold-Cranking Simulator, Apparent Viscosity @ -15 C, mPa.s, ASTM D5293 | 5290 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 158.4 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2021

ExxonMobil Egypt (S.A.E.)

1097 Cornish El-Nil, Garden City, Cairo, Egypt

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.global.mobil.com/en/contact-us>

+ 20 2 795 4850/60

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil 

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved