Mobil Super Moto™ Scooter 10W-30

Mobil Passenger Vehicle Lube , Hong Kong

Synthetic Technology Four-Stroke Scooter Engine Oil

Product Description

Mobil Super Moto™ Scooter 10W-30 is a high performance four-stroke engine oil by the makers of Mobil 1™. It is designed for modern scooter engine technology, aligned with development trends led by major OEMs.

Features and Benefits

Mobil Super Moto™ Scooter 10W-30 combines a unique blend of high quality mineral and synthesised hydrocarbon base oils together with an advanced additive system to provide excellent engine cleanliness, wear protection and effective corrosion prevention.

Mobil Super Moto™ Scooter is formulated to give you benefits and confidence of protection beyond that of conventional oils.
-7x Better Wear protection compared to industry standard *
-Provide Oil Drain Interval up to 6,000 km**
-Improve Fuel economy when switching from higher viscosity grade oils

*Based on Sequence IVA and Sequence VIII engine test results versus API SN specification
**Based on field trial conducted using 100/110/125 cc motorcycle models in India. Performance may vary depending on the engine design, temperature, fuel and actual riding condition.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Applications

Mobil Super Moto™ Scooter 10W-30 protects modern scooters with automatic transmission, especially protecting high power engines requiring JASO MB with API SN recommended by OEMs.

Specifications and Approvals

This product meets or exceeds the requirements of:
JASO MB
API SN

Properties and Specifications

Property	
Grade	SAE 10W-30
Viscosity Index, ASTM D2270	139
Density @ 15 C, g/ml, ASTM D4052	0.863
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	11.5
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.5

Property	
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	77.4
Flash Point, Cleveland Open Cup, °C, ASTM D92	232
Ash, Sulfated, mass%, ASTM D874	0.7
Total Base Number, mgKOH/g, ASTM D2896	6.7
Pour Point, °C, ASTM D97	-33
Mini-Rotary Viscometer, Apparent Viscosity, -30 C, mPa.s, ASTM D4684	19100

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2026

ExxonMobil Hong Kong
22nd Floor, Central Plaza,
18 Harbour Road, Wanchai
Hong Kong

+852 3197 8888
http://www.exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved