



Mobil Super Moto™ Scooter 10W-40

Mobil Passenger Vehicle Lube , India

Synthetic Technology Four-Stroke Scooter Engine Oil

Product Description

Mobil Super Moto™ Scooter 10W-40 is a high performance four-stroke engine oil, especially designed for modern scooter engine technology, aligned with development trends led by major OEMs.

Features and Benefits

Mobil Super Moto™ Scooter 10W-40 is a four stroke scooter engine oil blended by the makers of Mobil 1, with synthetic technology boosted by the latest API SN advanced additive technology. Mobil Super Moto Scooter 10W-40 is specially designed for smooth acceleration required in city traffic conditions with minimal vibrations.

Additionally, Mobil Super Moto™ Scooter 10W-40 provides superior protection even to high capacity engines with Heat Activated Anti-Wear Molecule™.

Heat-activated anti-wear molecule™ helps to maintain viscosity of the oil at high temperature to prevent engine wear.

Features	Advantages and Potential Benefits
Synthetic technology	Advanced formulation for performance in extreme conditions
Better engine protection	3 - way protection shields engine, transmission and clutch
Long engine life	Excellent wear, cleanliness and corrosion protection
Heat-activated anti-wear molecule™	Maintains viscosity of the oil at high temperature to prevent engine wear

Applications

Mobil Super Moto™ Scooter 10W-40 protects modern scooters with automatic transmission, especially protecting high power scooter engine.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SN
JASO MB

Properties and Specifications

Property	
Grade	SAE 10W-40
Mini-Rotary Viscometer, Apparent Viscosity, -30 C, mPa.s, ASTM D4684	21900
Density @ 15 C, g/ml, ASTM D1298	0.868

Property	
Pour Point, °C, ASTM D97	-33
Total Base Number, mgKOH/g, ASTM D2896	7.1
Viscosity Index, ASTM D2270	153
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.8
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 ⁽⁶⁾ sec ⁽⁻¹⁾ , mPa.s, ASTM D4683	4.2
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	101
Flash Point, Cleveland Open Cup, °C, ASTM D92	232
Ash, Sulfated, mass%, ASTM D874	0.8

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2025

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,

Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil 

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved