Mobil

Mobil Super™ 3000 Formula P 0W-20

Mobil Passenger Vehicle Lube , Iceland

High Protection Engine Oil

Product Description

Mobil Super™ 3000 engine oil series are synthetic and engineered to deliver outstanding protection.

Mobil Super 3000 Formula P 0W-20 is a new generation low ash–low viscosity engine oil formulated for the specific needs of Stellantis/ PSA most recent gasoline, diesel and hybrid vehicles. Mobil Super 3000 Formula P 0W-20 high protection engine oil holds PSA B71 2010 approval.

Features and Benefits

Mobil Super 3000 Formula P 0W-20 is designed to help:

- Modern gasoline, diesel and hybrid engines operate according to improved fuel economy and emission reduction targets
- Protect emission after-treatment systems from poisoning and clogging for long-life effectiveness (oil formula has reduced phosphorus, sulfur and metals (ash))
- Protect engines from deposits and sludge build-up for effective engine cooling and lubrication
- Preserve long engine life thanks to rapid start-up and effective protection of engines equipped with stop-start technology, even at cold temperature

Applications

Mobil Super 3000 Formula P 0W-20 is recommended for modern high efficiency gasoline, diesel and hybrid cars from Peugeot, Citroën, DS, and Opel (Vauxhall in the UK). This oil is recommended in particular for PSA DV5R and EB2DT engines with BlueHDi or PureTech technologies. Mobil Super 3000 Formula P 0W-20 is not appropriate for prior generation engines designed to operate with higher viscosity engine oils.

Owner's manual should be consulted for recommended viscosity grade and specification.

Specifications and Approvals

This product is recommended for use in applications requiring:
FIAT 9.55535-DM1
FIAT 9.55535-DSX

This product meets or exceeds the requirements of:
ACEA C5

Properties and Specifications

Property	
Grade	SAE 0W-20
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	8.3
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	42.8
Viscosity Index, ASTM D2270	170

Property	
Density @ 15 C, g/ml, ASTM D4052	0.846
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	229

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2026

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved