Mobil

Mobil 1™ 0W-40

Mobil Passenger Vehicle Lube , Laos

Ultimate Full Synthetic

Product Description

Mobil 1™ Triple Action Power+ is the ultimate full synthetic engine oil delivering outstanding engine Performance, Protection, and Cleanliness with the added benefit of Fuel Economy.

Features and Benefits

Why these matter for your engine:

• PERFORMANCE: Reduces the stress of daily wear and harsh conditions for longer engine life.
• PROTECTION: Guards against extreme temperatures to prevent breakdowns.
• CLEANLINESS: Prevents buildup of contaminants and sludge for a cleaner engine.

Mobil 1™ Triple Action Power+ is feature packed to:

• PERFORM: Long lasting power *
• PROTECT: 30X** better protection for high temperatures
• CLEAN: Prevents 99.9%*** of the harmful acid contaminants that damage your engine
• PLUS: Increases engine efficiency for advanced fuel economy when switching from higher viscosity oils.

* Based on MADs test program using internally specified drive cycles for 120,000 miles
** Based on Sequence IIIH vs industry limits
** Based on TBN/TAN measurements in vehicle testing. Results may vary by engine, driving conditions, and oil change interval.

Applications

Mobil 1™ Triple Action Power+ is suitable for use in petrol, diesel, and hybrid vehicles.

Always check your owner's manual for the recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
MB-Approval 229.5
VW 502 00
VW 505 00
NISSAN Genuine Performances
Porsche A40
GM dexosR

This product is recommended for use in applications requiring:
VW 503 01
API CF
FIAT 9.55535-M2

This product meets or exceeds the requirements of:
API SP
API SN PLUS
API SN
ACEA A3/B4
API SQ

Properties and Specifications

Property	
Grade	SAE 0W-40
Total Base Number, mgKOH/g, ASTM D2896	12.5
Ash, Sulfated, mass%, ASTM D874	1.2
Flash Point, Cleveland Open Cup, °C, ASTM D92	233
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	77
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.6
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	13.5
Density @ 15.6 C, g/ml, ASTM D4052	0.839
Viscosity Index, ASTM D2270	180
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	28200
Pour Point, °C, ASTM D97	-45

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2026

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved