



Mobil Delvac Legend™ 15W-40 Complete Defense

Mobil Commercial Vehicle Lube , Philippines

High Performance Diesel Engine Oil

Product Description

Mobil Delvac Legend™ 15W-40 Complete Defense is a high performance diesel engine oil that provides proven engine protection of diesel engines operating in on and off-highway severe service applications.

Mobil Delvac Legend 15W-40 Complete Defense is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

This product is fully compatible with Mobil Delvac Super 1300 15W-40 and can be used as a replacement of same.

Features and Benefits

The technology in Mobil Delvac Legend 15W-40 Complete Defense delivers excellent performance in both modern diesel engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Component compatibility	Longer gasket and seal life

Specifications and Approvals

This product is recommended for use in applications requiring:
ACEA E2
API CF-4
API CG-4
MB 228.1
VOLVO VDS

This product meets or exceeds the requirements of:
API SJ

Properties and Specifications

Property	
Grade	SAE 15W-40
Viscosity Index, ASTM D2270	136
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	106
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.2
Flash Point, °C, ASTM D92	220
Density @ 15 C, kg/l, ASTM D4052	0.88
Total Base Number, mgKOH/g, ASTM D2896	9
Pour Point, °C, ASTM D97	-27
Ash, Sulfated, mass%, ASTM D874	1.0

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved