



Mobil 1™ ESP X3 0W-40

Mobil Passenger Vehicle Lube , Slovakia

Advanced Full Synthetic Engine Oil

Product Description

Mobil 1™ ESP X3 0W-40 is an advanced full synthetic engine oil specifically designed to provide outstanding performance for high powered engines, providing outstanding engine cleanliness, wear protection, strong durability and advanced fuel economy*. Mobil 1 ESP X3 0W-40 is our latest technology developed in cooperation with Porsche, one of our key European Original Equipment Manufacturers (OEMs). Mobil 1 ESP X3 0W-40 has been expertly engineered to help prolong the life in new emerging gasoline powered European vehicles.

*compared to our Mobil 1 ESP Formula 5W-30 / Mobil 1 ESP 5W-30

Features and Benefits

Mobil 1 ESP X3 0W-40 is made with a proprietary blend of leading edge components formulated to be fully compatible with the latest Gasoline Particulate filters (GPF's). Mobil 1 ESP X3 0W-40 has been designed to help deliver outstanding performance and protection in conjunction with advanced fuel economy benefits. Key features and potential benefits include:

**Based on industry and OEM standard engine tests

| Features | Advantages and Potential Benefits |
|--|---|
| Active cleaning agents | Helps to prevent the buildup of harmful deposits to enable long and clean engine life** Provides outstanding engine cleanliness and sludge control |
| Outstanding high-temperature thermal and oxidation stability | Helps to reduce oil aging for protection throughout your oil drain interval |
| Enhanced frictional properties | Provides fuel economy improvement versus Mobil 1 ESP Formula 5W-30 |
| Excellent low temperature capabilities | Quick cold weather performance to help provide protection at start-up |
| Wear protection | Provides outstanding wear protection** |

Applications

Mobil 1 ESP X3 0W-40 is recommended for high-performance engines requiring GPFs (gasoline particulate filters).

- Mobil 1 ESP X3 0W-40 can only be used in the vehicles for which it is approved. It is not backward compatible with vehicle engines requiring an A40, C30 or C20 . ***

*** Always consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and specifications

Specifications and Approvals

| |
|--|
| This product has the following approvals: |
| PORSCHE C40 |

This product has the following approvals:

MB-Approval 229.51

MB-Approval 229.52

GM dexos2

This product meets or exceeds the requirements of:

FIAT 9.55535-S2

API SN PLUS

API SN

ACEA C3

Properties and Specifications

| Property | |
|---|-----------|
| Grade | SAE 0W-40 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.846 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 230 |
| Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683 | 3.8 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 14.1 |
| Pour Point, °C, ASTM D97 | -48 |
| Viscosity Index, ASTM D2270 | 204 |

Health and safety


Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved