Mobil

# Mobil Super™ 3000 Formula V 0W-20

Mobil Passenger Vehicle Lube , Serbia

Synthetic Engine Oil

## Product Description

The Mobil Super™ 3000 engine oil range is synthetic and engineered to deliver outstanding engine protection and performance.

Mobil Super™ 3000 Formula V 0W-20 is a high-performance engine oil specifically formulated to help extend engine life in modern gasoline and diesel vehicles equipped with exhaust after-treatment systems, such as Diesel Particulate Filters (DPFs). Its advanced low-viscosity formulation helps enhance fuel efficiency while providing excellent wear protection and engine cleanliness.

## Features and Benefits

Mobil Super™ 3000 Formula V 0W-20 is designed to help:

• Improve fuel economy in both gasoline and diesel engines
• Enhance engine cleanliness and help prevent sludge build-up
• Provide enhanced protection against high-temperature deposits and engine wear
• Deliver excellent cold-start performance for rapid lubrication and engine protection from start-up

## Applications

Mobil Super™ 3000 Formula V 0W-20 is suitable for modern, high-efficiency gasoline, diesel, and hybrid vehicles that specifically require an SAE 0W-20 viscosity grade and any of the specifications supported by this oil.

• Mobil Super™ 3000 Formula V 0W-20 is formulated to support the protection requirements of modern engine technologies, including downsized, turbocharged gasoline direct-injection (GDI) engines, helping to address challenges such as Low-Speed Pre-Ignition (LSPI).

• Mobil Super™ 3000 Formula V 0W-20 is not recommended for older engines designed to operate with higher-viscosity lubricants.

Always consult the vehicle owner's manual to confirm the recommended viscosity grade and performance specifications for your engine.

## Specifications and Approvals

| This product has the following approvals: |
|---|
| Porsche C20 |
| VW 509 00 |
| PORSCHE C20 |

| This product meets or exceeds the requirements of: |
|---|
| ACEA C5 |

## Properties and Specifications

| Property | |
|---|---|
| Grade | SAE 0W-20 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 8.3 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 44.1 |

| Property | |
|---|---|
| Pour Point, °C, ASTM D97 | -42 |
| Phosphorus, mass%, ASTM D4951 | 0.08 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 233 |
| Density @ 15 C, g/ml, ASTM D1298 | 0.845 |
| Ash, Sulfated, mass%, ASTM D874 | 0.8 |

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2026

.

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved