# Mobil Special™ Plus 5W-30

Mobil Passenger Vehicle Lube , Taiwan

Automotive Engine Oil

**Product Description**

Mobil Special™ Plus is a range of conventional engine oils that deliver engine protection and cleanliness. Mobil Special™ Plus is recommended for use in a wide range of applications and operating conditions.

**Features and Benefits**

• Helps reduce engine wear and corrosion

• Helps keep engine clean

• Multigrade motor oil allowing easier starts at low temperatures

• Good high temperature properties

**Applications**

Suitable for use in passenger car application using gasoline, CNG or LNG.

**Specifications and Approvals**

| This product meets or exceeds the requirements of: |
|---|
| API SN |

**Properties and Specifications**

| Property | |
|---|---|
| Grade | SAE 5W-30 |
| Viscosity Index, ASTM D2270 | 152 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.855 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 10.2 |
| Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684 | 17700 |
| Pour Point, °C, ASTM D97 | -45 |
| Total Base Number, mgKOH/g, ASTM D2896 | 6.7 |

| Property | |
|---|---|
| Ash, Sulfated, mass%, ASTM D874 | 0.7 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 234 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 62 |
| Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683 | 3.1 |

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2024
ExxonMobil international Holding Inc. Taiwan Branch
6F, No 2, Section 1, Tun Hua South Road
Taipei Taiwan

+886 2 2734 6888
http://www.exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved