MOBIL 1™ ADVANCED CLEAN SERIES

Mobil Passenger Vehicle Lube , United States

Advanced Full Synthetic Motor Oil

Product Description

Mobil 1 Advanced Clean motor oil utilizes our signature Triple Action Formula to deliver outstanding engine performance, protection, and cleanliness to vehicles of all ages. Specialty components in synthetic oil extend engine life by reducing deposits and sludge buildup—keeping critical engine parts clean and protected for up to 20,000 miles between oil changes.* Mobil 1 Advanced Clean motor oil meets ILSAC GF-7 standards, offering superior oxidation control, enhanced protection against pre-ignition and timing chain wear, and excellent cold-start and low-temperature performance. Mobil 1 is the #1 selling motor oil in America at retail,** trusted and recommended by car builders and experienced mechanics, and is the Official Motor Oil of NASCAR®.

Features and Benefits

• Cleans your engine in one oil change
• Helps extend engine life
• Protects for 20,000 miles – guaranteed*
• Prevents up to 100% of harmful sludge formation***
• Improves gas mileage****
• Keeps your engine running like new

Applications

• Mobil 1 Advanced Clean motor oils are recommended by ExxonMobil for applications in all types of modern gasoline-powered vehicles, including high-performance turbocharged, supercharged, multi-valve fuel injected engines found in passenger cars, SUVs, light vans and light trucks.
• Mobil 1 Advanced Clean is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.
• If your vehicle is covered by a warranty, follow the vehicle's oil life sensor or the oil change interval recommended in your owner's manual. Proper maintenance practices, including frequently checking the oil level to ensure that the appropriate amount of oil is present, are required to ensure effective performance.
• Always check your owner's manual for the manufacturer's recommended oil viscosity grade, API service classification and any builder approval.

*Protects for 20,000 miles or 1 year, whichever comes first
**Source: Circana/ Retail Tracking Service/ Dollar Sales/ 52 weeks ending February 1, 2025
***Based on Seq VH rocker cover sludge results
****vs GF-7 fuel economy requirement

Specifications and Approvals

This product has the following approvals:	0W-20	5W-20	5W-30
GM dexos1:GEN3 Licensed	X		X

This product is recommended for use in applications requiring:	0W-20	5W-20	5W-30
Fiat Chrysler Automotive MS-6395	X	X	X
Ford WSS-M2C945-A		X	
FORD WSS-M2C945-B1		X	
Ford WSS-M2C946-A			X
Ford WSS-M2C946-B1			X
Ford WSS-M2C947-A	X		

This product is recommended for use in applications requiring:	0W-20	5W-20	5W-30
Ford WSS-M2C947-B1	X		
FORD WSS-M2C960-A1		X	
FORD WSS-M2C961-A1			X
FORD WSS-M2C962-A1	X		
GM 6094M		X	

This product meets or exceeds the requirements of:	0W-20	5W-20	5W-30
API SJ			X
API SL		X	X
API SM		X	X
API SN	X	X	X
API SN PLUS	X	X	X
API SN PLUS RESOURCE CONSERVING	X	X	X
API SN Resource Conserving	X	X	X
API SP	X	X	X
API SP Resource Conserving		X	X
API SQ	X	X	X
API SQ Resource Conserving	X	X	X
ILSAC GF-7A	X	X	X
FORD WSS-M2C970-A1		X	
FORD WSS-M2C971-A1			X
FORD WSS-M2C972-A1	X		

Properties and Specifications

Property	0W-20	5W-20	5W-30
Grade	SAE 0W-20	SAE 5W-20	SAE 5W-30
Density @ 15.6 C, g/ml, ASTM D4052	0.8442	0.8491	0.8514
Flash Point, Cleveland Open Cup, °C, ASTM D92	227	229	234
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	8.2	8.6	9.75
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	43.11	47	56.69

Property	0W-20	5W-20	5W-30
Pour Point, °C, ASTM D97	-42	-39	-33

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2026

Exxon Mobil Corporation
22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved