



Mobil 1™ 0W-20

Mobil Passenger Vehicle Lube , Vietnam

Ultimate Full Synthetic

Product Description

Mobil 1™ Triple Action Power+ is the ultimate full synthetic engine oil delivering outstanding engine Performance, Protection, and Cleanliness with the added benefit of Fuel Economy.

Features and Benefits

Why these matter for your engine:

- **PERFORMANCE:** Reduces the stress of daily wear and harsh conditions for longer engine life
- **PROTECTION:** Guards against extreme temperatures to prevent breakdowns
- **CLEANLINESS:** Prevents buildup of contaminants and sludge for a cleaner engine

Mobil 1™ Triple Action Power+ is feature packed to:

- **PERFORM:** Long lasting power
- **PROTECT:** Up to 30X* better protection for high temperatures
- **CLEAN:** Prevents up to 99.9%** of the harmful acid contaminants that damage your engine
- **PLUS:** Increases engine efficiency up to 20%*** improved fuel economy

Mobil™ 1 0W-20 is engineered to enhance the performance and longevity of hybrid engines, offering:

- Excellent moisture handling capabilities under water & fuel contamination ****
- 3X better emulsion stability to protect against extreme conditions*****
- Excellent corrosion and rust protection under 10% water contamination*****
- 47% better anti-wear capabilities to provide greater protection against high frequency stop/start events*****

*Based on Sequence IIIH, against industry limits

**Based on oil change interval of 25,000 km conducted on certain vehicle model in the United States from 2024 to 2025

***Based on Sequence VIE against prior generation industry standard

**** Based on Filterability test

***** Based on Emulsion Retention Test at industry standard

***** Based on Copper Corrosion and Rust Protection Test at more stringent test conditions

***** Based on Seq. IVB, VIII, X

Applications

Mobil 1™ Triple Action Power+ is suitable for use in petrol, diesel, and hybrid vehicles.

Always check your owner's manual for the recommended viscosity grade and specifications for your particular vehicle

Specifications and Approvals

This product is recommended for use in applications requiring:
Ford WSS-M2C947-A
Ford WSS-M2C947-B1
FORD WSS-M2C962-A1
GM 6094M

This product meets or exceeds the requirements of:
API SP Resource Conserving
API SP
API SN PLUS
API SN
ILSAC GF-7A
API SQ
API SQ Resource Conserving
ACEA C5
ACEA C6
FORD WSS-M2C972-A1

Properties and Specifications

Property	
Grade	SAE 0W-20
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	17600
Pour Point, °C, ASTM D97	-48
Total Base Number, mgKOH/g, ASTM D2896	8.3
Ash, Sulfated, mass%, ASTM D874	0.7
Flash Point, Cleveland Open Cup, °C, ASTM D92	233
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	45.5
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.6
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.5
Density @ 15.6 C, g/ml, ASTM D4052	0.839
Viscosity Index, ASTM D2270	166

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2026

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil 

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved